# VIVIX-S Portable, Wired

Portable Flat Panel Detector For Digital Radiography



VIVIX-S Portable, Wired is a Vieworks' flat panel digital radiography cassette system with 14" x 17" coverage area for general radiographic applications using its unique image processing system and proprietary flat panel detector. With the same size as a film or a CR cassette, it is an excellent solution for upgrading conventional X-ray system. User friendly imaging software, VXvue™ is compliant with DICOM 3.0 standard and provides consistent image quality at a dramatically reduced dose and faster image information with optimized algorithm for each different study. It only takes a few simple steps to acquire and transmit images to the DICOM server through Gigabit Ethernet.



## VIVIX-S Portable, Wired

Portable Flat Panel Detector for Digital Radiography



#### **Features**

- \* Wide active area of 14" x 17"
- \* High spatial resolution with 140um pixel array
- \* Stable and reliable automatic exposure detection (Anytime<sup>TM</sup>)
- \* Viewer software running on Windows™ OS (VXvue™)
- \* Communication interface through Gigabit Ethernet (1000 BASE-T)
- \* Simple and easy integration with all kinds of digital radiography system



Configuration Detector System Control Unit

FXRD-1417SA/B FXRS-02A Designed and manufactured by Vieworks in Korea

### **Acquired Images**







#### Drawing



## **Technical Specification**

Application General radiography

Flat panel detector: a-Si TFT with PIN diode Technology

CsI:TI / Gd<sub>2</sub>O<sub>2</sub>S:Tb Scintillator 140um x 140um Pixel Pitch Pixels 2,560 x 3,072 pixels 14 x 17 inches (35 x 43cm) Image Size

A/D Conversion 14 bit Grayscale 16,384 steps X-ray Voltage Range 40 ~ 150kVp

X-ray Generator Interface Line trigger: DR Trigger Mode

> Auto trigger: AED (Automatic Exposure Detection) Mode Gigabit Ethernet (1000BASE-T) via PoE (Power over Ethernet)

Extension Cable GigE communication and power supply (7m)

Dimensions 460 (W) x 384 (L) x 15 (T) mm Approx. 2.9kg (GADOX) / 3.1kg (Csl) Weiaht Operating Environment 15 ~ 35°C, 30 ~ 85% RH (non-condensing)

Power DC24V, 0.5A

\* Specifications are subject to change without prior notification.



Data Interface











#### Headquarters

41-3, Burim-ro 170 beon-qil, Dongan-qu, Anyang-si, Gyeonggi-do, 431-060 Republic of Korea Tel +82-70-7011-6161 Fax +82-31-386-8631 E-mail sales@vieworks.com



